

BOGE S-4 series

Designed to take the lead



TECHNICAL DATA

BOGE type	Max. pressure bar	Effective free air delivery m ³ /min	Rated output		Dimensions W x D x H (mm)	Compressed air outlet	Weight with sound insulation kg	Weight with super sound insulation kg
			Main drive kW	Fan motor kW				
S 56-4 LF(D)	7.5	2.8 - 10.9	55	2.2	2380 (2780) x 1420 x 1990	DN 65	2150 (2410)	2170 (2430)
S 56-4 LF(D)	10	2.5 - 9.0	55	2.2	2380 (2780) x 1420 x 1990	DN 65	2150 (2410)	2170 (2430)
S 56-4 LF(D)	13	3.5 - 7.2	55	2.2	2380 (2780) x 1420 x 1990	DN 65	2150 (2410)	2170 (2430)
S 56-4 L(D)	7.5	10.1	55	2.2	2330 (2780) x 1420 x 1990	DN 65	2070 (2310)	2090 (2330)
S 76-4 (D)	7.5	14.1	75	2.2	2330 (2780) x 1420 x 1990	DN 65	2160 (2420)	2180 (2440)
S 76-4 (D)	10	12.5	75	2.2	2330 (2780) x 1420 x 1990	DN 65	2160 (2420)	2180 (2440)
S 76-4 (D)	13	10.4	75	2.2	2330 (2780) x 1420 x 1990	DN 65	2160 (2420)	2180 (2440)
S 76-4 LF(D)	7.5	2.9 - 14.4	75	2.2	2380 (2780) x 1420 x 1990	DN 65	2150 (2410)	2170 (2430)
S 76-4 LF(D)	10	2.8 - 12.3	75	2.2	2380 (2780) x 1420 x 1990	DN 65	2150 (2410)	2170 (2430)
S 76-4 LF(D)	13	2.6 - 10.4	75	2.2	2380 (2780) x 1420 x 1990	DN 65	2150 (2410)	2170 (2430)
S 90-4 (D)	7.5	16.5	90	3.0	2330 (2780) x 1420 x 1990	DN 65	2260 (2520)	2280 (2540)
S 90-4 (D)	10	15.0	90	3.0	2330 (2780) x 1420 x 1990	DN 65	2260 (2520)	2280 (2540)
S 90-4 (D)	13	12.6	90	3.0	2330 (2780) x 1420 x 1990	DN 65	2260 (2520)	2280 (2540)
S 90-4 LF(D)	7.5	2.9 - 16.6	90	3.0	2380 (2780) x 1420 x 1990	DN 65	2250 (2510)	2270 (2530)
S 90-4 LF(D)	10	2.8 - 14.7	90	3.0	2380 (2780) x 1420 x 1990	DN 65	2250 (2510)	2270 (2530)
S 90-4 LF(D)	13	2.7 - 12.8	90	3.0	2380 (2780) x 1420 x 1990	DN 65	2250 (2510)	2270 (2530)
S 110-4 (D)	10	17.1	110	3.0	2330 (2780) x 1420 x 1990	DN 65	2260 (2520)	2280 (2540)
S 110-4 (D)	13	15.2	110	3.0	2330 (2780) x 1420 x 1990	DN 65	2260 (2520)	2280 (2540)
S 110-4 LF(D)	7.5	5.8 - 19.2	110	3.0	2380 (2780) x 1420 x 1990	DN 65	2250 (2510)	2270 (2530)
S 110-4 LF(D)	10	2.8 - 16.3	110	3.0	2380 (2780) x 1420 x 1990	DN 65	2250 (2510)	2270 (2530)
S 110-4 LF(D)	13	2.8 - 14.4	110	3.0	2380 (2780) x 1420 x 1990	DN 65	2250 (2510)	2270 (2530)
S 110-4 L(D)	7.5	19.3	110	3.0	2330 (2780) x 1420 x 1990	DN 65	2170 (2430)	2190 (2450)

All models are available without or with an integrated dryer (D).

BOGE S-4 series

Designed to take the lead



TECHNICAL DATA

BOGE type	Max. pressure bar	Effective free air delivery m ³ /min	Rated output		Dimensions W x D x H (mm)	Compressed air outlet	Weight with sound insulation kg	Weight with super sound insulation kg
			Main drive kW	Fan motor kW				
S 91-4	7.5	17.7	90	3.0	2930 x 1620 x 1990	DN 80	3450	3500
S 91-4	10	15.8	90	3.0	2930 x 1620 x 1990	DN 80	3450	3500
S 91-4 LF	7.5	5.4 - 18.5	90	3.0	2980 x 1620 x 1990	DN 80	3550	3600
S 91-4 LF	10	5.3 - 16.5	90	3.0	2980 x 1620 x 1990	DN 80	3550	3600
S 111-4	7.5	21.1	110	3.0	2930 x 1620 x 1990	DN 80	3550	3600
S 111-4	10	17.8	110	3.0	2930 x 1620 x 1990	DN 80	3550	3600
S 111-4	13	15.4	110	3.0	2930 x 1620 x 1990	DN 80	3550	3600
S 111-4 LF	7.5	5.5 - 21.5	110	3.0	2980 x 1620 x 1990	DN 80	3550	3600
S 111-4 LF	10	5.3 - 18.8	110	3.0	2980 x 1620 x 1990	DN 80	3550	3600
S 111-4 LF	13	4.9 - 15.4	110	3.0	2980 x 1620 x 1990	DN 80	3550	3600
S 111-4 L	7.5	20.7	110	3.0	2930 x 1620 x 1990	DN 80	3450	3500
S 132-4	7.5	24.5	132	3.0	2930 x 1620 x 1990	DN 80	3650	3700
S 132-4	10	22.2	132	3.0	2930 x 1620 x 1990	DN 80	3650	3700
S 132-4	13	18.5	132	3.0	2930 x 1620 x 1990	DN 80	3650	3700
S 132-4 LF	7.5	5.5 - 25.0	132	3.0	2980 x 1620 x 1990	DN 80	3650	3700
S 132-4 LF	10	5.3 - 22.2	132	3.0	2980 x 1620 x 1990	DN 80	3650	3700
S 132-4 LF	13	5.0 - 18.5	132	3.0	2980 x 1620 x 1990	DN 80	3650	3700
S 132-4 L	10	20.6	132	3.0	2930 x 1620 x 1990	DN 80	3550	3600
S 160-4	7.5	28.4	160	5.5	2930 x 1620 x 1990	DN 80	3700	3750
S 160-4	10	25.4	160	5.5	2930 x 1620 x 1990	DN 80	3700	3750
S 160-4	13	21.2	160	5.5	2930 x 1620 x 1990	DN 80	3700	3750
S 160-4 LF	7.5	5.5 - 28.1	160	5.5	2980 x 1620 x 1990	DN 80	3750	3800
S 160-4 LF	10	5.3 - 25.1	160	5.5	2980 x 1620 x 1990	DN 80	3750	3800
S 160-4 LF	13	5.0 - 22.3	160	5.5	2980 x 1620 x 1990	DN 80	3750	3800
S 160-4 L	13	19.3	160	5.5	2930 x 1620 x 1990	DN 80	3600	3650